

Ausführung wie Bauer-ID.: 170G0772. Bitte prüfen Sie die An- bzw. Einbaumöglichkeit anhand des beigefügten Maßbildes.

Bauer Article No.: 188H8944

Helical-gear motor

Type	: BG06-31/D06LA8/SP		
Motor power	(kW) : 0,04	Mounting	: B5/V1
Output shaft speed	(rpm) : 10,5	Terminal box position	: III / C
Torque	(Nm) : 36,0	Dimensional drawing	: BG06
Service factor fB	: 1,25	Catalogue	: DG 07
Corrosion protection	: Standard	net weight per unit	: ca. 9,5 kg
Painting	: RAL 5015		
ambient temperature	°C : -20 - +40		
Add./Special design:	Mounting B5 inclined 30° to mounting V1.		

Gear design:

Type	: BG06 2 -staged Helical gear
Design code 31	: with standard flange on side front (d: 120 mm) : solid output shaft on gear side front (d: 17 mm)
Total gear reduction i	: 66,79
Oil-type/-volume (l)	: CLP 220 / 0,15

Design of the motor:

Type	: Three-phase squirrel cage motor D06LA8		
Voltage	(V) : 400	Rated speed	(rpm) : 680
Connection	: Y	IP prot. type per EN 60529	: IP 65
Frequency	(Hz) : 50	IC cool. type EN 60034-6	: IC 411
Rated current	(A) : 0,31	Design acc. to DIN VDE 0530-1/EN 60034-1	
Power factor (cos phi)	: 0,55	Terminal box size	: KAG2
Temperature class	: F		

Please note:

Motor

Motor connection by means of CAGE-CLAMP.
CAGE CLAMP is a Registered Trademark of the company WAGO